




Ficha Técnica



Pigtail de Fibra Óptica Multimodo / Monomodo

Especificaciones

Tipo de conectores	SC	LC	FC	ST
Tipo de fibra	62.5/125m	9/125m		50/125m
Max.Insertion Loss	≤0.3dB	≤0.2dB		≤0.3dB To
Typ.Insertion Loss	≤0.2dB	≤0.15dB		≤0.2dB
Typ.Return Loss	≥35dB	PC≥45dB UPC≥55dB APC≥60dB		≥35dB
Cable retention (900um)	2 lbs	2 lbs		2 lbs
Matung Durability (1000cycles)	<0.2dB	<0.2dB		<0.2dB
Ferrule Material	Ceramic	Ceramic		Ceramic
Housing Material	Composite	Composite		Composite
Operating Temperature (°C)	-40°C to +80°C	-40°C to +80°C	-40°C to +80°C	-40°C to +80°C



- Todos los cables son 100% testeados ópticamente con etiquetado individual.
- Variedad de fibra y tipos de cables disponibles.
- Variedad de tipos y colores disponibles.

OM-1 (62.5/125) Gris

OM-2 (52/125) Naranja

OM-3 (52/125) Turquesa

OM-4 (52/125) Violeta

OS-2 (9/125) Amarillo